

V1 FIRE MANAGEMENT SYSTEM

FOR SURFACE ROCKET LAUNCHERS

The Version 1 (V1) Fire Management System allows for the control of up to two LAND-LGR4 "Fletcher" Launchers from up to 100 feet away with the ability to individually select and fire any of the eight available launcher tubes. With a redundant safety switch configuration and dual firing triggers, unintentional rocket ignition is next to impossible. The unit has multiple options for power, including the 5590 battery and connectivity to vehicle systems power. The control enclosures and cables are EMI/RFI resistant and designed for the harshest of environments.



DIMENSIONS

Length _ _ _ _ _ 8.66 in / 22.0 cm
Width _ _ _ _ _ 4.72 in / 12.0 cm
Height _ _ _ _ _ 3.58 in / 9.1 cm
Weight _ _ _ _ _ 4.5 lbs / 2.04 kg



COMPONENTS

- Firing Control Box
- Junction Box
- Remote Cables (Standard 20 & 100 foot)
- Power/Battery Cable
- Firing Cable

Remote cable lengths can be adjusted to meet users integration requirements. Prices will vary according to length.

P/N: 2018500

NSN: 1230-01-687-6224

FEATURES

- Intuitive Controls
- MIL-DTL-26482 II Connectors
- Environmental EMI/RFI Backshells and Cabling
- Tethered Environmental Dust Caps
- Redundant Safety Switch Configuration
- Multiple Power Supply Options
- Individual Rocket Selection
- Rugged Blast Proof Enclosures
- 5590 Battery Power Option
- Operational Status LED Indicator
- Replacable Fuse for Power Supply Protection